



**CertainTeed**

**sustainable**  **insulation.**

# Residential and Commercial Insulation Products

## Submittal Form



Submitted to: \_\_\_\_\_

Job name: \_\_\_\_\_

Submitted by: \_\_\_\_\_

Date: \_\_\_\_\_

This Submittal Form is provided to assist you in specifying and selecting the proper CertainTeed Insulation products. Basic product descriptions and performance data are included. For further information or technical assistance, contact your local CertainTeed representative.

CertainTeed Corporation, P.O. Box 860, Valley Forge, PA 19482

**1-800-233-8990**

Visit our web site at: [www.certainteed.com/insulation](http://www.certainteed.com/insulation)

Customer Service 1-800-441-9850 • Fax 1-800-735-2381

Many of CertainTeed's Manufacturing plants are registered to ISO 9001:2000 standards.

**CertainTeed**  
SAINT-GOBAIN

**Product**      **Description**      **R-Values and Thicknesses\***      **Applicable Standards**

**Unfaced Building Insulation**

Sustainable Insulation® manufactured in widths to permit pressure fit installation. Used with a separate vapor retarder or where no vapor retarder is required or recommended.

	R	Nominal Thickness
<input type="checkbox"/>	49	15"
<input type="checkbox"/>	38	12"
<input type="checkbox"/>	38C**	10¼"
<input type="checkbox"/>	30	10"
<input type="checkbox"/>	30C**	8¼"
<input type="checkbox"/>	25	8"
<input type="checkbox"/>	22	6½"

\*\*Cathedral Ceiling Batt

	R	Nominal Thickness
<input type="checkbox"/>	21	5½"
<input type="checkbox"/>	20	5½"
<input type="checkbox"/>	19	6¼"
<input type="checkbox"/>	15	3½"
<input type="checkbox"/>	13	3½"
<input type="checkbox"/>	11	3½"

Complies with ASTM C665, Type I. Is noncombustible, meeting test criteria of ASTM E136. Thermal performance determined by ASTM C653 and C518.

**Kraft Faced Building Insulation**

Sustainable Insulation® manufactured with a kraft paper facing with a vapor permeance rating of 1.0 or less. Includes stapling flanges.

	R	Nominal Thickness
<input type="checkbox"/>	38	12"
<input type="checkbox"/>	38C**	10¼"
<input type="checkbox"/>	30	10"
<input type="checkbox"/>	30C**	8¼"
<input type="checkbox"/>	25	8"
<input type="checkbox"/>	22	6½"

\*\*Cathedral Ceiling Batt

	R	Nominal Thickness
<input type="checkbox"/>	21	5½"
<input type="checkbox"/>	20	5½"
<input type="checkbox"/>	19	6¼"
<input type="checkbox"/>	15	3½"
<input type="checkbox"/>	13	3½"
<input type="checkbox"/>	11	3½"

Complies with ASTM C665, Type II, Class C, Category 1. Thermal performance determined by ASTM C653 and C518.

**SpeedyR™ Kraft Faced Building Insulation**

Sustainable Insulation® manufactured with a kraft paper facing with a vapor permeance rating of 1.0 or less. No stapling required.

	R	Nominal Thickness
<input type="checkbox"/>	21	5½"
<input type="checkbox"/>	19	6¼"
<input type="checkbox"/>	13	3½"

Complies with ASTM C665, Type II, Class C, Category 1. Thermal performance determined by ASTM C653 and C518.

**Masonry Wall Insulation**

Sustainable Insulation® unfaced batts designed for use behind paneling in masonry-type construction where cavity depth is limited by the furring strips. Used with a separate vapor retarder or where no vapor retarder is required or recommended.

	R	Nominal Thickness
<input type="checkbox"/>	6	1¾"
<input type="checkbox"/>	6	¾"

Complies with ASTM C665, Type I. Is noncombustible, meeting test criteria of ASTM E136. Thermal performance determined by ASTM C653 and C518.

\*Additional R-values & thicknesses may be available. Contact your CertainTeed representative for more information.

Product	Description	R-Values and Thicknesses*	Applicable Standards
---------	-------------	---------------------------	----------------------

**Basement Wall Insulation**

Sustainable Insulation® available with perforated white flame resistant polypropylene or foil facings. Used to insulate walls of unfinished crawlspaces and basements. Flame spread rating is 25 or less. Available in 48" and 72" widths.

R	Nominal Thickness
11	3¾"

Complies with ASTM C665, Type II, Class A, Category 2. Thermal performance determined by ASTM C653 and C518.

**MemBrain™ Smart Vapor Retarder and Air Barrier Film**

Vapor retarder sheeting intended for use with unfaced, vapor permeable mass insulation (fiber glass and mineral wool) in wall and ceiling cavities. MemBrain is a polyamide film that changes its permeability with ambient humidity conditions.

Roll Width	Nominal Thickness
8 ft.	2 mil
9 ft.	2 mil
10 ft.	2 mil
12 ft.	2 mil

Water vapor permeance values are determined by ASTM E96.  
 ≤ 1.0 perm (57 ng/Pa•s•m²) (ASTM E96, Standard Desiccant method)  
 > 10 perms (570 ng/Pa•s•m²) (ASTM E96, Standard Water method)

NoiseReducer™ Products	Description	R-Values and Thicknesses*	Applicable Standards
------------------------	-------------	---------------------------	----------------------

**Sound Attenuation Batts**

Sustainable Insulation® unfaced batts manufactured in widths to permit pressure fit installation in steel stud systems.

R	Nominal Thickness
11	3½"
8	2½"

Complies with ASTM C665, Type I. Is noncombustible, meeting test criteria of ASTM E136. Thermal performance determined by ASTM C653 and C518.

**Acoustical Ceiling Batts**

Sustainable Insulation® 24" x 48" batts either unfaced or with tabless kraft paper facing. For use in suspended ceiling systems.

R	Nominal Thickness
19	6¼"
11	3½"

Complies with ASTM C665, Type I (unfaced), Type II, Class C, Category 1, (faced). Thermal performance determined by ASTM C653 and C518.

**NoiseReducer™**

Residential Sustainable Insulation® batts are available with a white kraft facing for easy attachment to interior wood stud framing.

R	Nominal Thickness
11	3½"

Complies with ASTM C665, Type II, Class C, Category 2. Thermal performance determined by ASTM C653 and C518.

Commercial Products	Description	R-Values and Thicknesses*	Applicable Standards
---------------------	-------------	---------------------------	----------------------

**CertaPro™ AcoustaTherm™ Batts**

Sustainable Insulation® manufactured in widths to permit friction fit installation. Unfaced is used with a separate vapor retarder or where no vapor retarder is required or recommended.

R	Nominal Thickness
30 (Unfaced)	10"
19 (Unfaced, Kraft-faced no tabs)	6¼"
11 (Unfaced, Kraft-faced no tabs)	3½"
8 (Unfaced)	2½"

Unfaced complies with ASTM C553, Type I, ASTM C665, Type I and is noncombustible, per ASTM E136. Kraft Faced complies with ASTM C665, Type II, Class C, Category 1. Thermal performance determined by ASTM C518.

\*Additional R-values & thicknesses may be available. Contact your CertainTeed representative for more information.

Commercial Products	Description	R-Values and Thicknesses*	Applicable Standards														
<input type="checkbox"/> <b>CertaPro™ Partition Batts</b>	Sustainable Insulation® unfaced flexible blanket-type batts for use in commercial construction for acoustical and thermal insulation in shaft and partition walls.	<input type="checkbox"/> <table border="1"> <thead> <tr> <th>R</th> <th>Nominal Thickness</th> </tr> </thead> <tbody> <tr> <td>5.8</td> <td>1½"</td> </tr> </tbody> </table>	R	Nominal Thickness	5.8	1½"	Complies with ASTM C553, Type I, II, ASTM C665, Type I and is noncombustible, per ASTM E136.										
R	Nominal Thickness																
5.8	1½"																
<input type="checkbox"/> <b>CertaPro™ Thermal Kraft Faced Batts</b>	Sustainable Insulation® manufactured with a flanged kraft paper facing providing a vapor retarder with a perm rating of 1.0 or less.	<input type="checkbox"/> <table border="1"> <thead> <tr> <th>R</th> <th>Nominal Thickness</th> </tr> </thead> <tbody> <tr> <td>19</td> <td>6¼"</td> </tr> <tr> <td>11</td> <td>3½"</td> </tr> </tbody> </table>	R	Nominal Thickness	19	6¼"	11	3½"	Complies with ASTM C553, Type I and ASTM C665, Type II, Class C, Category 1. Thermal performance determined by ASTM C177 or ASTM C518.								
R	Nominal Thickness																
19	6¼"																
11	3½"																
<input type="checkbox"/> <b>CertaPro™ Thermal Foil Faced Batts</b>	Sustainable Insulation® manufactured with a flanged foil/kraft vapor retarder providing a perm rating of 0.05 or less. Has a flame spread rating of 75 or less.	<input type="checkbox"/> <table border="1"> <thead> <tr> <th>R</th> <th>Nominal Thickness</th> </tr> </thead> <tbody> <tr> <td>38</td> <td>12"</td> </tr> <tr> <td>30</td> <td>10"</td> </tr> <tr> <td>19</td> <td>6¼"</td> </tr> </tbody> </table> <input type="checkbox"/> <table border="1"> <thead> <tr> <th>R</th> <th>Nominal Thickness</th> </tr> </thead> <tbody> <tr> <td>13</td> <td>3½"</td> </tr> <tr> <td>11</td> <td>3½"</td> </tr> </tbody> </table>	R	Nominal Thickness	38	12"	30	10"	19	6¼"	R	Nominal Thickness	13	3½"	11	3½"	Complies with ASTM C553, Type I and ASTM C665, Type III, Class B, Category 1. Thermal performance determined by ASTM C177 and ASTM C518.
R	Nominal Thickness																
38	12"																
30	10"																
19	6¼"																
R	Nominal Thickness																
13	3½"																
11	3½"																
<input type="checkbox"/> <b>CertaPro™ Thermal FSK-25 Faced Batts</b>	Sustainable Insulation® manufactured with a flanged flame resistant foil-scrim-kraft facing. Used where a flame spread rating of 25 or less is required for insulation facings. The facing has a perm rating of 0.02 or less.	<input type="checkbox"/> <table border="1"> <thead> <tr> <th>R</th> <th>Nominal Thickness</th> </tr> </thead> <tbody> <tr> <td>38</td> <td>12"</td> </tr> <tr> <td>30</td> <td>10"</td> </tr> <tr> <td>19</td> <td>6¼"</td> </tr> </tbody> </table> <input type="checkbox"/> <table border="1"> <thead> <tr> <th>R</th> <th>Nominal Thickness</th> </tr> </thead> <tbody> <tr> <td>13</td> <td>3½"</td> </tr> <tr> <td>11</td> <td>3½"</td> </tr> </tbody> </table>	R	Nominal Thickness	38	12"	30	10"	19	6¼"	R	Nominal Thickness	13	3½"	11	3½"	Complies with ASTM C553, Type I and ASTM C665, Type III, Class A, Category 1. Thermal performance determined by ASTM C177 or ASTM C518.
R	Nominal Thickness																
38	12"																
30	10"																
19	6¼"																
R	Nominal Thickness																
13	3½"																
11	3½"																
<input type="checkbox"/> <b>CertaPro™ Thermal Extended Flange FSK Faced, White PSK Faced Batts</b>	Sustainable Insulation® manufactured with a white flame-resistant poly-scrim-kraft facing (PSK) or flame-resistant foil-scrim-kraft facing (FSK). Used where a flame spread rating of 25 or less is required for insulation facings. All facings have a perm rating of 0.02 or less and a 4" extended flange.	<input type="checkbox"/> <table border="1"> <thead> <tr> <th>R</th> <th>Nominal Thickness</th> </tr> </thead> <tbody> <tr> <td>30 (FSK only)</td> <td>10"</td> </tr> <tr> <td>19 (PSK &amp; FSK)</td> <td>6¼"</td> </tr> </tbody> </table>	R	Nominal Thickness	30 (FSK only)	10"	19 (PSK & FSK)	6¼"	PSK & FSK comply with ASTM C553, Type 1. PSK complies with ASTM C665, Type II, Class A, Category 1. FSK complies with ASTM C665, Type III, Class A, Category 1. Thermal performance determined by ASTM C177 and ASTM C518.								
R	Nominal Thickness																
30 (FSK only)	10"																
19 (PSK & FSK)	6¼"																

Product	Description	R-Values and Thicknesses*	Specification Compliance
---------	-------------	---------------------------	--------------------------

<input type="checkbox"/> <b>CertaPro™ Commercial Board</b>	Flexible to rigid boards for residential and commercial construction. Manufactured unfaced, with a reinforced white kraft and foil laminate (ASJ) or an aluminum foil, glass scrim kraft laminate (FSK). Available in four densities: CB 150: Light weight, used where flexibility is desired. CB 225: Semi-rigid board type. CB 300: Board type with greater rigidity and compressive strength for a smoother more abuse resistant surface. CB 600: A rigid board product.	<table border="1"> <thead> <tr> <th colspan="2">CB 150</th> <th colspan="2">CB 225</th> <th colspan="2">CB 300</th> <th colspan="2">CB 600</th> </tr> <tr> <th>R-Value</th> <th>Thickness</th> <th>R-Value</th> <th>Thickness</th> <th>R-Value</th> <th>Thickness</th> <th>R-Value</th> <th>Thickness</th> </tr> </thead> <tbody> <tr> <td>16.0</td> <td>4"</td> <td>17.4</td> <td>4"</td> <td>17.4</td> <td>4"</td> <td>—</td> <td>—</td> </tr> <tr> <td>14.0</td> <td>3½"</td> <td>15.2</td> <td>3½"</td> <td>15.2</td> <td>3½"</td> <td>—</td> <td>—</td> </tr> <tr> <td>12.0</td> <td>3"</td> <td>13.0</td> <td>3"</td> <td>13.0</td> <td>3"</td> <td>—</td> <td>—</td> </tr> <tr> <td>10.0</td> <td>2½"</td> <td>10.9</td> <td>2½"</td> <td>10.9</td> <td>2½"</td> <td>—</td> <td>—</td> </tr> <tr> <td>8.0</td> <td>2"</td> <td>8.7</td> <td>2"</td> <td>8.7</td> <td>2"</td> <td>9.1</td> <td>2"</td> </tr> <tr> <td>6.0</td> <td>1½"</td> <td>6.5</td> <td>1½"</td> <td>6.5</td> <td>1½"</td> <td>6.8</td> <td>1½"</td> </tr> <tr> <td>—</td> <td>—</td> <td>4.3</td> <td>1"</td> <td>4.3</td> <td>1"</td> <td>4.5</td> <td>1"</td> </tr> </tbody> </table>	CB 150		CB 225		CB 300		CB 600		R-Value	Thickness	R-Value	Thickness	R-Value	Thickness	R-Value	Thickness	16.0	4"	17.4	4"	17.4	4"	—	—	14.0	3½"	15.2	3½"	15.2	3½"	—	—	12.0	3"	13.0	3"	13.0	3"	—	—	10.0	2½"	10.9	2½"	10.9	2½"	—	—	8.0	2"	8.7	2"	8.7	2"	9.1	2"	6.0	1½"	6.5	1½"	6.5	1½"	6.8	1½"	—	—	4.3	1"	4.3	1"	4.5	1"	<table border="1"> <thead> <tr> <th>Product</th> <th>ASTM C612</th> <th>ASTM C553</th> </tr> </thead> <tbody> <tr> <td>CB 150</td> <td>Type IA</td> <td>Types I, II &amp; III</td> </tr> <tr> <td>CB 225</td> <td>Type IA</td> <td>—</td> </tr> <tr> <td>CB 300</td> <td>Types IA &amp; IB</td> <td>—</td> </tr> <tr> <td>CB 600</td> <td>Types IA &amp; IB</td> <td>—</td> </tr> </tbody> </table> <p>ASTM C1136 (Facing only) Type II: FSK; Type I: ASJ</p>	Product	ASTM C612	ASTM C553	CB 150	Type IA	Types I, II & III	CB 225	Type IA	—	CB 300	Types IA & IB	—	CB 600	Types IA & IB	—
CB 150		CB 225		CB 300		CB 600																																																																																				
R-Value	Thickness	R-Value	Thickness	R-Value	Thickness	R-Value	Thickness																																																																																			
16.0	4"	17.4	4"	17.4	4"	—	—																																																																																			
14.0	3½"	15.2	3½"	15.2	3½"	—	—																																																																																			
12.0	3"	13.0	3"	13.0	3"	—	—																																																																																			
10.0	2½"	10.9	2½"	10.9	2½"	—	—																																																																																			
8.0	2"	8.7	2"	8.7	2"	9.1	2"																																																																																			
6.0	1½"	6.5	1½"	6.5	1½"	6.8	1½"																																																																																			
—	—	4.3	1"	4.3	1"	4.5	1"																																																																																			
Product	ASTM C612	ASTM C553																																																																																								
CB 150	Type IA	Types I, II & III																																																																																								
CB 225	Type IA	—																																																																																								
CB 300	Types IA & IB	—																																																																																								
CB 600	Types IA & IB	—																																																																																								

\*Additional R-values & thicknesses may be available. Contact your CertainTeed representative for more information.

**Product**

**Description**

**R-Values and Thicknesses\***

**Specification Compliance**



**CertaPro™ AcoustaBoard™ Black†**

Rigid or semi-rigid fiber glass board with a black mat facing for acoustical applications in sound studios or other acoustically sensitive applications requiring a black exposed surface.

Available in two densities:

Semi-rigid board type.

Board type with greater rigidity and compressive strength for a smoother more abuse resistant surface.

Type 225		Type 300	
R-Value	Thickness	R-Value	Thickness
8.7	2"	8.7	2"
6.5	1½"	6.5	1½"
4.3	1"	4.3	1"

Product	ASTM C612
Type 225	Type IA
Type 300	Types IA & IB



**CertaPro™ AcoustaBlanket™ Black†**

1/2" to 2" thick black fiber glass blanket with a durable fire-resistant black composite surface used for acoustical control applications in theaters, sound studios or other acoustically sensitive applications requiring a black exposed surface.

Type 150	Type 200
Thickness	Thickness
1"	—
1½"	½"
2"	—

Complies with ASTM C553, Type I and II. Acoustical performance determined by ASTM C423 using Type A mounting. Thermal resistance determined by ASTM C177 or C518.



**Metal Building Insulation 202-96†**

A flexible blanket insulation furnished in rolls and intended to be laminated on one side with a suitable vapor retarder. It is used as a thermal and acoustical insulation in the roofs and sidewalls of pre-engineered metal buildings and post frame construction. Plain unfaced, Metal Building Insulation 202-96 may be used as an additional layer of insulation over laminated metal building insulation in systems or over the top of BUR or single ply roofs in metal reroof applications to achieve greater thermal performance.

R	Nominal Thickness	Widths	Lengths
<input type="checkbox"/> 30	9¼"	36", 48", 60", 72"	25'
<input type="checkbox"/> 25	8"	36", 48", 60", 72"	30'
<input type="checkbox"/> 21	6¾"	36", 48", 60", 72"	45'
<input type="checkbox"/> 19	6¾"	36", 48", 60", 72"	50'
<input type="checkbox"/> 16	5½"	36", 48", 60", 72"	50'
<input type="checkbox"/> 13	4¾"	36", 48", 60", 72"	75'
<input type="checkbox"/> 11	3¾"	36", 48", 60", 72"	100'
<input type="checkbox"/> 10	3¾"	36", 48", 60", 72"	100'

Metal Building Insulation 202-96 has physical properties that regularly meet the requirements of the following specifications: ASTM C991, Type I Plain and NAIMA 202-96. (Rev. 2000)



**Commercial Blanket Insulation†**

This product is used as a thermal or acoustical insulation in commercial buildings where wide rolls of unfaced insulation are required such as retrofitting a warehouse. It is also used in post frame construction. In roofs and sidewalls this product can be used as a second layer over the unfaced side of Metal Building Insulation 202-96.

Additionally, it may be installed over old roof decks (BUR and metal) prior to application of a new standing seam roof.

Limitations: This product is not intended to be laminated with vapor retarder facing and does not meet the requirements of NAIMA 202-96.

R	Nominal Thickness	Widths	Lengths
<input type="checkbox"/> 30	10"	48", 60", 72"	25'
<input type="checkbox"/> 25	8"	48", 60", 72"	40'
<input type="checkbox"/> 21	6½"	48", 60", 72"	45'
<input type="checkbox"/> 19	6¼"	48", 60", 72"	50'
<input type="checkbox"/> 11	3½"	48", 60", 72"	100'

Has physical properties that regularly meet the requirements of the following specifications: ASTM C553, Type I and ASTM C665, Type I. ASTM C665, Type I.

† Indicates Sustainable Insulation product may not be available in all areas

\*Additional R-values & thicknesses may be available. Contact your CertainTeed representative for more information.

Premium Blowing Wool Products		Description	R-Values*	Bags per 1,000 sq. ft.	Minimum Weight Pounds per sq. ft.	Min. Installed/Settled Thickness	Applicable Standards
<input type="checkbox"/>	<b>InsulSafe® SP</b>	Fiber glass blowing insulation for pneumatic application in open attics or closed cavities.	60	31.4	0.972	22.00"	Complies with ASTM C764, Type I. Thermal performance is determined by ASTM C687 and ASTM C518. Is noncombustible, meeting criteria of ASTM E136.
			49	25.2	0.780	18.50"	
			44	22.4	0.695	16.75"	
			38	19.1	0.591	14.50"	
			30	14.9	0.462	11.75"	
			22	10.8	0.334	8.75"	
			19	9.3	0.289	7.75"	
13	6.2	0.192	5.25"				
<input type="checkbox"/>	<b>OPTIMA® System</b>	System including OPTIMA premium fiber glass blowing insulation and OPTIMA non-woven fabric or equivalent.	15	18.8	0.525	3.50" (2 x 4)	Complies with ASTM C764, Type I. Thermal performance is determined by ASTM C687 and ASTM C518. Is noncombustible, meeting criteria of ASTM E136.
			23	29.5	0.825	5.50" (2 x 6)	
			30	38.8	1.088	7.25" (2 x 8)	
			39	49.6	1.388	9.25" (2 x 10)	
			47	60.3	1.688	11.25" (2 x 12)	
			56	71.0	1.988	13.25" (2 x 14)	

Spray Foam Products		Description	R-Values and Thicknesses*									
<input type="checkbox"/>	<b>CertaSpray® Open Cell Foam</b>	A two-component water blown spray polyurethane foam applied as a spray insulation. The foam provides thermal insulation for the interior of buildings and reduces air infiltration through the building envelope.	<b>R</b>	<b>Thickness in</b>	<b>R</b>	<b>Thickness in</b>	<b>R</b>	<b>Thickness in</b>	<b>R</b>	<b>Thickness in</b>	<b>R</b>	<b>Thickness in</b>
			3.7	1	11.2	3	18.7	5	30.0	8	45.0	12
			5.6	1.5	13.1	3.5	20.6	5.5	33.7	9		
			7.4	2	15.0	4	22.5	6	37.5	10		
			9.3	2.5	16.9	4.5	26.2	7	41.2	11		
<input type="checkbox"/>	<b>CertaSpray® Closed Cell Foam</b>	A two-component HFC-245fa blown spray polyurethane foam applied as a spray insulation. The foam provides thermal insulation for the interior of buildings and reduces air infiltration through the building envelope.	<b>R</b>	<b>Thickness in</b>	<b>R</b>	<b>Thickness in</b>	<b>R</b>	<b>Thickness in</b>	<b>R</b>	<b>Thickness in</b>	<b>R</b>	<b>Thickness in</b>
			6.4	1	19.2	3	32.0	5	51.2	8	76.8	12
			9.6	1.5	22.4	3.5	35.2	5.5	57.6	9		
			12.8	2	25.6	4	38.4	6	64.0	10		
			16.0	2.5	28.8	4.5	44.8	7	70.4	11		

Complies with ASTM C1029 Type II

## Product Characteristics

### Sound Transmission Loss

CertainTeed's Fiber Glass products can reduce sound transmission when properly installed in construction assemblies and can add from 3 to 12 points to the STC rating depending on the type of assembly. The actual rating is dependent on the workmanship, mass of total material, thickness of insulation and the air tightness of the construction. In wood stud assemblies, separation of the wall

surfaces plus the addition of insulation in stud cavities are the most effective means of reducing sound transmission. This may be accomplished by installing resilient channels on one side of the partition, or with staggered or double wall constructions. The table on the following page lists some typical sound rated partition assemblies.

\*Additional R-values & thicknesses may be available. Contact your CertainTeed representative for more information.

## Product Characteristics (continued)

### Surface Burning Characteristics

These products have the following maximum flame spread and smoke developed ratings when tested per ASTM E84:

Product	Flame Spread	Smoke Developed
Unfaced Building Insulation	5	0
UltraTherm®	5	0
InsulSafe® SP	5	5
OPTIMA®	5	5
FSK-25 Building Insulation	25	50
Basement Wall Insulation	25	50
Standard Foil Faced Building Insulation	75	150
MemBrain™	20	55
DryRight™	<25	<50
CertaSpray™ Open Cell Foam	<25	<450
CertaSpray™ Closed Cell Foam	<25	<450

FSK-25, Basement Wall and standard foil-faced insulation products have a critical radiant flux flame propagation resistance equal to or greater than 0.12 w/cm<sup>2</sup>.

### Fire Safety

CertainTeed Unfaced Fiber Glass Building Insulation, OPTIMA®, InsulSafe® SP, and UltraTherm® are noncombustible per ASTM E136 test criteria.

Many building codes require that foam plastic insulation be covered with an approved 15-minute thermal barrier. Consult local building code officials to ensure the application meets local building codes and regulations.

## Approximate STC Ratings

### Wood Frame Partitions With Gypsum Wallboard Facings (1/2" & 5/8")

	No Insulation		3 1/2" of CertainTeed Fiber Glass Insulation (batts or blown)	
	1/2"	5/8"	1/2"	5/8"
Single studs/single layer facings	34	35	39	38
Single studs/resilient channel	39	40	46	50
Staggered studs/single layer facings	39	43	50	51
Double stud walls/single layer facings	46	45	57	57

### Steel Stud Partitions With Gypsum Wallboard Facings (1/2" & 5/8")

	No Insulation				3 1/2" of CertainTeed Fiber Glass Insulation (batts or blown)			
	16" O.C.		24" O.C.		16" O.C.		24" O.C.	
	2 1/2" Studs	3 5/8" Studs	2 1/2" Studs	3 5/8" Studs	2 1/2" Studs	3 5/8" Studs	2 1/2" Studs	3 5/8" Studs
Single layer facings	36	39	36	39	45	47	48	50
Double layer one side, single layer other side	39	44	42	47	51	52	52	55
Double layer each side	45	48	50	52	55	57	55	58

## Guide Specifications for CertainTeed Fiber Glass Thermal and Acoustical Insulations

Note to the specifier: Provide information as required; delete inappropriate items and fill in where indicated.

This guide specification applies to thermal and acoustical insulation in walls, ceilings and floors. It follows Construction Specifications Institute (CSI) format.

### PART 1 – GENERAL

- 1.01 **Work included**  
State type of insulation and where it is to be installed.
- 1.02 **Related Work**  
State if separate vapor retarder and/or air barrier is to be installed.
- 1.03 **References**  
Include appropriate insulation standards.

### PART 2 – PRODUCTS

#### 2.01 Acceptable Manufacturers

CertainTeed Corporation

#### 2.02 Materials

##### Thermal Insulation

Insulation for (ceilings) (walls) (floors) shall be CertainTeed \_\_\_\_\_ inches thick, with R-Value of \_\_\_\_\_, or Insulation for (ceilings) (or other approved location) shall be CertainTeed \_\_\_\_\_ installed at minimum of \_\_\_\_\_ inches thick, with \_\_\_\_\_ bags/1,000 sq. ft. for R-Value of.

##### Sound Control Insulation

Insulation for (ceilings) (walls) (floors) shall be CertainTeed \_\_\_\_\_.

##### Acoustical Ceiling Batts

Insulation over suspended ceilings shall be CertainTeed kraft-faced (3 1/2" R-11) (6 1/4" R-19) Acoustical Ceiling Batts.

### PART 3 – EXECUTION

#### 3.01 Preparation

Verify that mechanical and electrical services in (ceilings) (walls) (floors) have been installed and tested and, if appropriate, verify that adjacent materials are dry and ready to receive insulation.

#### 3.02 Installation

Installation shall be in accordance with CertainTeed's instructions.



# Guide Specifications for CertainTeed Commercial Fiber Glass Insulation Products

## PART 1 – GENERAL

### 1.01 Summary

A. This section includes commercial building thermal/acoustical insulation for application to:

1. Exterior building walls;
2. Interior partition walls, shaft walls, and other interior surfaces;
3. Ceiling suspension systems.

### 1.02 Submittals

- A. Prepare and submit for approval information as required by the conditions of the contract and Division 1 Submittals sections.
- B. Submit product data for each thermal and acoustical insulation product specified.

### 1.03 Quality Assurance

A. Installers shall be qualified to perform work of this section and shall be experienced in the performance of installation operations as appropriate to the project.

### 1.04 Delivery and Storage

A. Deliver all insulation materials and accessories to the project site in manufacturer's original, unopened, undamaged packaging, with all identification labels intact. Store in a safe place protected from dust, dirt, moisture and physical abuse before and during installation.

## PART 2 – PRODUCTS

### 2.01 Approved Manufacturer and Products

- A. All thermal/acoustical insulation materials shall be in accordance with Division 1 Submittals, manufactured by CertainTeed Corporation, including but not limited to:
1. CertaPro AcoustaTherm Batts, Unfaced or Kraft Faced (no tabs).
  2. CertaPro Partition Batts, Unfaced.
  3. CertaPro Thermal Kraft Faced Batts.
  4. CertaPro Thermal Foil Faced Batts.
  5. CertaPro Thermal FSK-25 Faced Batts.
  6. CertaPro Thermal Extended Flange Batts, FSK Faced.

7. CertaPro Thermal Extended Flange Batts, Black PSK Faced.
  8. CertaPro Thermal Extended Flange Batts, White PSK Faced.
  9. Building Insulation, Unfaced, Kraft Faced.
  10. CertaPro Commercial Board, Unfaced, FSK Faced, ASJ Faced.
  11. CertaPro AcoustaBoard Black.
  12. CertaPro AcoustaBlanket Black.
  13. Metal Building Insulation 202-96 (Rev. 2000).
  14. Commercial Blanket Insulation.
- B. Where applicable, specify product thicknesses and length/width dimensions so insulation completely fills wall cavities to meet thermal and acoustical performance specifications.
- C. Specify type of vapor retarder facing to meet water vapor transmission and fire rating specifications.

### 2.01 Products and Applications

- A. Curtain Wall Insulation:
1. CertaPro AcoustaTherm Batts, Unfaced or Kraft Faced (no tabs).  
R-Value: \_\_\_\_\_.
  2. CertaPro Thermal Kraft, Foil, or FSK-25 Faced Batts.  
R-Value: \_\_\_\_\_.
  3. CertaPro Commercial Board, Unfaced, FSK or ASJ Faced.  
R-Value: \_\_\_\_\_.
- B. Partition Insulation:
1. CertaPro Partition Batts, Unfaced.  
R-Value: 5.8.
- C. Interior Cavity Wall Insulation:
1. CertaPro AcoustaTherm Batts, Unfaced or Kraft Faced.  
R-Value: \_\_\_\_\_.
  2. CertaPro Thermal Batts, Kraft, Foil, or FSK-25 Faced.  
R-Value: \_\_\_\_\_.
  3. CertaPro Thermal Extended Flange Batts, FSK or PSK Faced.  
R-Value: \_\_\_\_\_.
- D. Insulation over ceiling suspension systems:
1. CertaPro AcoustaTherm Batts, Unfaced or Kraft Faced (no tabs).  
R-Value: \_\_\_\_\_.

E. Insulation for acoustic control in theaters, sound studios, etc.:

1. CertaPro AcoustaBoard Black.  
R-Value: \_\_\_\_\_.
  2. CertaPro AcoustaBlanket Black.  
R-Value: \_\_\_\_\_.
- F. Insulation for metal building ceiling and side wall applications:
1. CertainTeed Metal Building 202-96 (Rev. 2000).  
R-Value: \_\_\_\_\_.
  2. Commercial Blanket Insulation.  
R-Value: \_\_\_\_\_.

## PART 3 – EXECUTION

### 3.01 Inspection

- A. Verify that all insulation may be installed in accordance with project drawings, thermal and acoustical design requirements and fire ratings.
- B. Confirm that all exterior and interior wall, partition, and floor/ceiling assembly construction has been completed to the point where the insulation may be correctly installed.

### 3.02 Installation

B. Install all insulation in compliance with manufacturer's published instructions and good workmanship so that acoustical and thermal performance requirements are met.

### 3.03 Safety Precautions

- A. Properly protect insulation contractor's employees during installation of all insulation. Protection shall include proper attire when handling and applying insulation materials, and shall include but not be limited to gloves, hard hats, disposable dust respirators, and eye protection.
- B. Conduct all job site operations in compliance with applicable provisions of the Occupational Safety and Health Act and/or local safety and health codes and regulations.



**ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:**

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS  
GYPSUM • CEILINGS • INSULATION • PIPE

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777  
[www.certainteed.com/insulation](http://www.certainteed.com/insulation)

**CertainTeed**  
SAINT-GOBAIN